



LUBRIVAC 130P

Swarf and oil vacuum with pump out system

- *Powerful industrial vacuum for liquids and swarf*
- *Separate outlet pump for liquid discharge*
- *Integrated sieve basket for solid / liquid separation*
- *2nd stage fluid filtration 100 micron*
- *Detachable container for easy disposal operations*
- *Powerful single-phase motors*
- *Automatic level stop*



ACCESSORY KIT



SCRAPER



AUTO LEVEL



BASKET



OUTLET

The LUBRIVAC 130P is a robust single phase industrial vacuum that can vacuum and separate fluids from swarf debris. The LUBRIVAC 130P has a separate discharge pump which can also be used simultaneously whilst vacuuming. Fitted with: micro –pierced stainless steel carbon swarf/solids basket, TNT second stage filtration for a filtration of 300 micron that allows fluids (oil, emulsions) to remain in the lower part of the collecting tank, electrical level indicator that immediately stops the unit as the maximum liquid level of 130 liters is reached in the container. The LUBRIVAC 130P includes as standard a range of accessories including: flexible hose, conical lance, scraping nozzle and discharging valve for fluid filling/discharging. The Lubrivac 130P give significant benefits in reducing oil, coolant consumption and associated costs.



<i>Technical data</i>		LUBRIVAC 130
Power supply	V - Hz	230 - 50
Power / Potenza	kW	2.4
Max vacuum	mbar	216
Max air flow	l/min	5500
Suction inlet / Ø	mm	50
Liquids capacity	Litres	130
Solids capacity	Litres	38
Suction rate	l/sec	130/30
Noise level	dbA	76
Weight	Kg	100
Dimensions	cm	116 x 82 x 133

