

LUBRISPIN EC1000

MANUAL SWARF CENTRIFUGE

The LUBRISPIN EC1000 is constructed for long lasting continuous operating. The machine housing is of a robust design with quality steel. The Centrifuge is powered directly by a central positioned heavy-duty motor. The unit has an interlocked cover to prevent opening the pneumatic lid during processing, central suspension, 2mm perforated tipping basket + lifting hook, soft start, out of balance sensor, emergency stop switch and signal lamp lights.

Suitable for de-oiling of metal chips and parts. Drying efficiency of up to 1% is possible.

Other applications: drying, rinsing, **degreasing, washing, coating.**

Specifications: Model EC1000

| | |
|-------------------------|-------------|
| Max load weight: | 100Kg |
| Basket capacity: | 85L |
| Time cycle: | 3 -5 mins |
| Standard speed | 700 RPM |
| Motor: | 3.6KW, IP55 |
| Heater option: | +3.2KW |
| Electrical: | 400V/50Hz |
| Certification: | CE approved |

Standard Features

- Removable galvanized basket 630mm dia
- Soft start and stop
- Self-braking motor, un-balance sensor
- Automatic electric system (complete with: stop / start control, emergency stop, interlocked, timer, soft start)
- Boxed electric-system with protection to IP44
- Pneumatic lid opening
- Meets the latest EU legislation regulations

Options

- Heating for viscous oils
- Lift and tilt basket hook
- Jib crane and hoist
- Extra baskets
- Wheeled basket carts



