

# LUBRISPIN EC500

The LUBRISPIN EC500 is constructed for long lasting continuous operating. The machine housing is of a robust design with quality steel. The Centrifuge is powered directly by a central positioned heavy-duty motor. The unit has an interlocked cover to prevent during processing, 2mm perforated basket + lifting hook, emergency stop switch and signal lamp lights.

Suitable for de-oiling of metal chips and parts. Drying efficiency of up to 1% is possible.

Other applications: drying, rinsing, **degreasing, washing, coating.**



## Specifications: Model EC500

<b>Max load weight:</b>	50Kg
<b>Basket capacity:</b>	56L
<b>Time cycle:</b>	Variable / 3 mins
<b>Standard speed</b>	700 RPM
<b>Motor:</b>	1.5KW, IP55
<b>Heater option:</b>	+3.2KW
<b>Electrical:</b>	400V/50Hz
<b>Certification:</b>	CE approved
<b>Dimensions mm:</b>	H945, W630, D945
<b>Weight:</b>	150Kg

## Standard Features

- Removable galvanized basket H330 x 475mm diameter
- Solid cast iron base plate
- Self-braking motor
- Automatic electric system (complete with: stop / start control, emergency stop, interlocked, timer, thermal relay and warning lights)
- Boxed electric-system with protection to IP44
- Meets latest EU legislation and regulations

## Options

- Heating for viscous oils
- Speed control
- Jib crane and hoist
- Extra baskets
- Wheeled basket carts
- Pneumatic lid operation



